

# FIRST AID FOR PIPE LEAKS



**FAST PRESSURIZED  
LEAK SEALING  
UP TO 435 PSI**



## **AVOID ENVIRONMENTAL CONTAMINATION WITH SEALBALL**

Our system is designed to adapt to all forms of pipe to be sealed, including areas with welds, elbows and T's

## **ADVANTAGE OF SEALBALL**

Fast installation even under pressure  
no additional load to pipe, adjusts to  
out-of-round pipe

## **SEALBALL APPLICATIONS**

Effective at elbows, corners and T's

Fluids: water, oil and gas

Maximum Temperature: 176° F / 80°C

Maximum Pressure: 435psi / 30bar



A Product of



**technofink**

Manufactured in USA

# OPERATING INSTRUCTIONS

## SEALBALL 2" TO 4" KIT

## SEALBALL 4" TO 8" KIT

## SEALBALL 8" TO 50" KIT

( 1 ) -Select the required size for the pipe diameter and place ratchets on the same side and away from the leak (within a safe distance) with cranking handles pointing outwards. ( 2 ) -Insert strap through slot in center spool of the ratchet and pull through a minimum of 5" ( 3 ) -Start ratcheting both handles - by raising and lowering handle - leaving a gap between the strap and the pipe. ( 4 ) -Slide the opposite side of Sealball slowly to align to the opposite side of the leak. Place ball between strap and pipe and locate Seal ball close to the leak and crank ratchet to close gap. ( 5 ) -Slowly roll the ball sideways over the hole using the strap and roll the ball up and down to position the ball right over the hole. Crank the ratchet just tight enough to seal the leak.



**CAUTION:** Wear all personal protection equipment necessary, including but not restricted to safety gloves, face shield, safety glasses, long sleeves shirts when operating Sealball. Do not overtighten ratchets. Inspect ratchets, balls and straps visually for any damage. **DO NOT USE IF DAMAGED.**

**GCS Galvotec**  
CORROSION SERVICES, LLC

300 Bark Drive • Harvey, LA 70058 • [www.galvoteccorrosion.com](http://www.galvoteccorrosion.com)  
Phone.: (504) 362-7373 • Fax: (504) 362-7331 • Email: [Service@galvoteccorrosion.com](mailto:Service@galvoteccorrosion.com)